


**PPL 8050SS\***



IP20



**Example of Code** 8050SS.LL.TS.35.90.1.N.M.

Main Code	Lighting Type	Watt	CCT	CRI	Finishes	Driver	Cover Option
<b>8050SS*</b> Suspended	<b>WL</b> - Without Light		<b>27</b> - 2700K	<b>8</b> - ≥ 80	<b>1</b> - White	<b>N</b> - Non Dim*****	
	<b>LL****</b> - Linear Light with opal diffuser	Please choose your wattage from the pages 280	<b>30</b> - 3000K	<b>9</b> - ≥ 90	<b>2</b> - Grey	<b>DA</b> - DALI*****	<b>P</b> - Plastic cover with screws
	<b>FS*****</b> - Fixed Spotlight	Please choose your product and wattage from the pages 46 and 66	<b>35</b> - 3500K		<b>3</b> - Black		<b>M</b> - Metal cover with magnet
	<b>TS*****</b> - Track Spotlight	Please choose your product and wattage from the pages 38 and 62	<b>40</b> - 4000K		<b>4</b> - Special Colour** <b>5</b> - Aluminium Eloxal		

- Notes**
- \* PPL 8050SS is a project - based special production product that should be measured according to the project. Please share your project or a drawing that shows the parts of the product you need
  - \*\* On request
  - \*\*\* Page 347 A'Line PPL 9032 products are suitable for this system
  - \*\*\*\* Page 50 Minor and Page 74 Sargas products are suitable for this system
  - \*\*\*\*\* Page 38 Minor and Page 68 Sargas products are suitable for this system
  - \*\*\*\*\* Driver is inside the aluminium body